

SAFE-GUARD™

INSPECTION DOORS

Access Door For Belt Cleaner Inspections & Blade Change Outs



Chute Inspection and Access Doors are a necessary part of any transfer point to allow for safe inspection and access to maintain the belt cleaner systems.



45 degree flange on interior of door prevents fines from accumulating.



Door closed.



Door opened. Safety screen closed.



Door opened. Safety screen opened.

- **Safety** - inspection screen guard standard on every door for the ability to safely inspect equipment while it is running.
- **Redesigned Frame** - has a 45 degree flange to shed fines from accumulating on the interior of the door.
- **Low Profile Steel Construction** - with a dual EPDM dust seal that can withstand temperatures from -40 degrees F to 200 degrees F.
- **Available in 3 standard sizes:** 12" x 12", 12" x 18" and 18" x 24".
- **Heavy Duty Available in sizes:** 12" x 18", 18" x 24", 24" x 24" and 24 x 36".
- **Bolted** - hinged inspection screen

Heavy Duty Inspection Door also available.



Inspection Door Part Numbers

Part Number	Description
M-ASG-SID-12X12	12"x12" Insp. Door
M-ASG-SID-12X18	12"x18" Insp. Door
M-ASG-SID-18X24	18"x24" Insp. Door

Add an Inspection Door to your existing head chute for safe access to cleaners and chute clean-out.