

Secondary Belt Cleaners


www.asgco.com

Are installed after the point where the belt leaves the head (discharge) pulley and or anywhere on the return side of the belt where it can be cleaned and maintained effectively.

Secondary Cleaners	TORO®	Razor-Back®	Razor-Back MDX®	Chevron™
Belt Width	18"-48" 450-1200 mm	18"-96" 450-2400 mm	18"-96" 450-2400 mm	36"-96" 900-2400 mm
Belt Speed	<1000 fpm 5m/sec.	< 1000 fpm 5m/sec.	< 1200 fpm 6m/sec.	< 500 fpm 2.5m/sec.
Secondary Tensioners				
Bolt-Up™	YES	YES	YES	NO
Duo-Spring™	YES	YES	YES	YES
Bolt-Up MDX	NO	NO	NO	YES
Air-Shoc™ (Secondary)	NO	NO	NO	YES
Spring-Shoc™ (Secondary)	NA	NA	NA	NA
Belt Conditions				
OK on reversible belt?	YES	NO	NO	YES
Blade Materials				
TORO™ Urethane	YES	YES	N/A	N/A
TORO™ F-Tips	YES	YES	N/A	N/A
TORO™ C-Tips	YES	YES	N/A	N/A
F-Tips	YES	YES	N/A	N/A
C-Tips	YES	YES	N/A	N/A
V-Tips	N/A	N/A	N/A	N/A
MDX F-Tips	N/A	YES	YES	N/A
MDX C-Tips	N/A	YES	YES	N/A
MDX V-Tips	N/A	YES	YES	N/A



Secondary Blades

Blade Materials										
Blade Type	TORO®	TORO® F-Tips	TORO® C-Tips	F-Tips	C-Tips	V-Tips	MDX F-Tips	MDX C-Tips	MDX V-Tips	Chevron (Std/Ntd)
Belt Speed	< 1000 fpm < 5 m/sec	< 1000 fpm < 5 m/sec	< 1000 fpm < 5 m/sec	< 1000 fpm < 5 m/sec	< 1000 fpm < 5 m/sec	< 1000 fpm < 5 m/sec	< 1200 fpm < 6 m/sec	< 1200 fpm < 6 m/sec	< 1200 fpm < 6 m/sec	200-500 fpm < 2.5 m/sec
Temperature Range	-20-180°F -28 to 82°C	-20-180°F -28 to 82°C	-20-180°F -28 to 82°C	-20-400°F -28 to 204°C	-20-400°F -28 to 204°C	-20-400°F -28 to 204°C	-20-400°F -28 to 204°C	-20-400°F -28 to 204°C	-20-400°F -28 to 204°C	-20-250°F -28 to 121°C
Use w/Mech. Fasteners	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	No	Yes

Secondary Belt Cleaner Tensioners

Bolt-Up™	Duo-Spring™	Bolt-Up™ MDX	Spring-Shoc™	Air-Shoc™
				
- All 304 stainless steel construction - Lifetime Warranty - Visual tension check	- All 304 stainless steel construction - Lifetime Warranty - Push-up or Pull-up tensioning options	- All 304 stainless steel HD construction - Lifetime Warranty - Visual tension check	- All 304 stainless steel HD construction - Lifetime Warranty - Rubber and UHMW impact bushings	- All 304 stainless steel HD construction - Lifetime Warranty - Rubber and UHMW impact bushings

